NEPTUNE SAND FILTERS

DESIGNED BY AUSTRALIANS FOR AUSTRALIAN CONDITIONS

Neptune for swimming pools

By Pool Pro

Simply A Better Choice!

PUMPS | FILTERS | CHLORINATORS | CLEANERS | ACCESSORIES | CHEMICALS | SPA PRODUCTS | MAINTENANCE PRODUCTS | SPARE PARTS

Neptune for swimming pools

By Pool Pro

Neptune Sand Filters are made of spun fibreglass, are built to last and include many great features:

- Stainless steel clamp lock designed to allow 360 degree rotation to assist with installation.*
- Top diffuser ensures even distribution of water over the filter media.
- Oil filled lower mount pressure gauge.
- Materials are reliable, non-corrosive and designed for all weather conditions.
- UV treated to be able to work in direct sunlight.
- Suitable for all filter media; sand, zeolite and glass.
- Warranty: 10 years on tank, 2 years on multi port valve for SF500-SF800.

*Only for models SF500 & SF650.

PRODUCT INFORMATION

Filter Size	Model	Valve Type	Valve Port Size	Filter Area (m^2)	Max Flow Rate
20 inch	SF500	Standard	40mm / 1.5"	0.22	185 Lpm 11.10m^3/h
25 inch	SF650	Standard	40mm / 1.5"	0.32	260 Lpm 15.60m^3/h
28 inch	SF700	Standard	50mm / 2.0"	0.40	336 Lpm 20.16m^3/h
32 inch	SF800	Standard	50mm / 2.0"	0.50	415 Lpm 24.9m^3/h
36 inch	ECSF900	Standard	50mm / 2.0"	0.64	520 Lpm 31.20m^3/h
36 inch	ECSF900C	Standard	65mm / 2.5"	0.64	533 Lpm 32.00m^3/h
48 inch	ECSF1200	Standard	50mm / 2.0"	1.13	860 Lpm 51.60m^3/h
48 inch	ECSF1200C	Standard	65mm / 2.5"	1.13	941 Lpm 56.50m^3/h

PRODUCT DIMENSIONS

Model	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Filter media quantity required (guide only)			
							Sand Kg / Bags	Zeolite Kg / Bags	Coarse Glass Kg / Bags	Fine Glass Kg / Bags
20 inch SF500	535	500	845	670	730	235	80 / 4	60 / 4	25 / 2	40 / 3
25 inch SF650	635	500	950	775	835	300	140 / 7	105 / 7	45 / 3	60 / 4
28 inch SF700	723	500	1092	877	960	390	220 / 11	165 / 11	60 / 4	105 / 7
32 inch SF800	800	780	1200	1002	1085	425	360 / 18	270 / 18	105 / 7	165 / 11
36 inch ECSF900	900	780	1300	1090	1172	480	470 / 24	345 / 24	150 / 10	225 / 15
36 inch ECSF900C	900	780	1334	1145	1242	480	470 / 24	345 / 24	150 / 10	225 / 15
48 inch ECSF1200	1200	1000	1600	1468	1550	740	860 / 43	645 / 43	270 / 18	405 / 27
48 inch ECSF1200C	1200	1000	1634	1368	1620	740	860 / 43	645 / 43	270 / 18	405 / 27

This is a guide only. Sand size may differ from country to country and therefore sand weights may vary.

DIAGRAM - SF500 / SF650



DIAGRAM - SF700 / SF800



DIAGRAM - ECSF900 / ECSF1200



TECHNICAL INFORMATION

FUNCTIONS : Refer to 6-Way Multi-port Valve	
Max Working Pressure	250kPa / 36psi / 2.5bar
Factory Testing Pressure	400kPa / 58psi / 4.0bar
Max Water Temperature	43°C (109°F)
Size of Silica Sand	0.5-0.8mm
Max Filtration Velocity	50mm^3 / h / m^2

AVAILABLE FROM YOUR LOCAL POOL PRO STOCKIST

PUMPS | FILTERS | CHLORINATORS | CLEANERS | ACCESSORIES | CHEMICALS | SPA PRODUCTS | MAINTENANCE PRODUCTS | SPARE PARTS

Pool Pro

Celebrating 25+ YEARS SINCE 1993

Simply A Better Choice

Phone Free Call: 1800 143 788 **International Phone:** + 61 7 3209 7884

Fax: 1800 778 820 **Email:** office@poolpro.com.au **Web:** www.poolpro.com.au